



Atlantic Kleen 512LFM

Extremely Heavy-Duty, Oil Rejecting Alkaline Cleaner

Atlantic Kleen 512LFM is a concentrated blend of alkaline builders, dispersants, water conditioners, demulsifiers, and low foaming detergents balanced for maximum soil penetration and removal. Atlantic Kleen 512LFM is formulated for use in all multi-stage immersion, electrolytic, and recirculating industrial wash systems. Atlantic Kleen 512LFM is suitable for use on ferrous metals, including cast iron, as well as titanium, stainless steel, copper, and other metals which are resistant to strong alkali. Atlantic Kleen 512LFM is NON-FOAMING under normal use conditions, however, Atlantic Kleen 512LFM may foam if sprayed at high pressure and temperatures below 120°F. Atlantic Kleen 512LFM offers excellent particle soil removal, very good oil rejection, and provides convenience and economy as a liquid cleaner. Atlantic Kleen 512LFM is suitable for automatic chemical feeding, and is very effective with specialty Thin-Film™ oil removal equipment that demands a thin, non-adulterated oil film to perform properly.

- Formulated with oil rejecting surfactants and detergents for outstanding tank life.
- Cleans all soils; including paraffins, sterates, heavy greases, mild rust, and soluble oils.
- Offers completely foam-free immersion cleaning.
- Contains an specialty oil rejecting additive to split soluble mineral and vegetable oils.
- One of the best spray cleaners for heavy smut and grease ever developed.
- Performs extremely well in soak cleaning and electrolytic cleaning applications.

PROPERTIES:

Appearance:	Light yellow to amber liquid
Specific Gravity:	1.23 (Very high concentrate)
pH(1%):	>12.0
Biodegradability:	Detergents are 100% biodegradable.
Oil Rejection Capability:	>99.5%

USE INFORMATION:

Concentration:	0.5-6.0%	Spray	2.0-8.0%	Immersion
Temperature:	120-200°F	Spray	80-200°F	Immersion
Contact Time:	As available			

PRECAUTIONS: May cause severe burns to the skin and eyes upon contact. ****AVOID CONTACT** FOR INDUSTRIAL USE ONLY!** Refer to MSDS.

PACKAGE: Bulk, 275, 55, 30, 15, and 5-Gallon Containers.

Atlantic Specialty Chemicals Corporation
317 Godwin Avenue Midland Park, NJ 07432
800-440-7550