



Atlantic RP 295LN

EXTREMELY SAFE and EFFECTIVE RUST PROTECTOR

Atlantic RP 295LN is a unique blend of anti-oxidants and mild alkaline buffers designed to provide up to, and in most cases over, 90 days indoor rust protection by leaving a dry, non-oily, non-waxy clear film on ferrous components. Atlantic RP 295LN may be applied by either conventional recirculating spray or immersion. The Atlantic RP 295LN rust protecting film is thin enough not to interfere with normal dimensional measurements. Atlantic RP 295LN is water soluble, making it rinsable in pressurized or agitated water if further painting or processing of the component is required. Atlantic RP 295LN provides unequalled rust protection among aqueous, non oil systems, exceeding nitrite amine combinations and some oil systems without the expense, V.O.C.'s, and hazards involved. Atlantic RP 295LN performs by forming a hydrate on the metals surface repelling humidity and accidental water mist contact.

PRODUCT PROPERTIES:

Appearance:	Clear liquid, odor nil.
Specific Gravity:	1.22
Solubility:	Complete
Flash Point:	None
pH(1%):	9.0
HIMS:	1,0,0

USE INFORMATION:

Concentration:	
Immersion	5-15% by volume
Spray:	5-15% by volume
Temperature:	Ambient to 150°F (Heat above 100°F accelerates drying)
Contact Time:	As available (Usually 1 minute or less)

PRECAUTIONS:

May cause irritation to the eyes upon contact.
****AVOID CONTACT** FOR INDUSTRIAL &
COMMERCIAL USE ONLY!**

PACKAGE:

Bulk, 275, 55, 30, 15, and 5-gallon plastic containers.

Atlantic Specialty Chemicals Corporation
317 Godwin Avenue Midland Park, NJ 07432
800-440-7550